



TOOLBOX TALK



LADDER SAFETY INSPECT LADDERS CAREFULLY

All ladders *must* be inspected for defects and/or damage periodically by a competent person, and after an occurrence that could affect their safe use.

Ladder users *must* inspect ladders before each use, and defective and/or damaged ladders *must* either be immediately marked in a manner that readily identifies them as defective/damaged, or be tagged with a "Do Not Use" tag or tag containing similar language. Defective and/or damaged ladders *must* not be used and *must* be removed from service until repaired.

Look for warning signs. Check all ladder components for signs of wear, corrosion and structural failure before each use. These inspections should include:

- Rungs - Check for broken, split, cracked, corroded or missing rungs.
- Side Rails - Check for broken, split, cracked, corroded or missing side rails.
- Cracks - Check carefully for cracks; they are hard to see. Cracks weaken ladders.
- Excessive Bends - Check for rungs or side rails with excessive bends. Bent areas are greatly weakened and may fail during use.
- Hardware - Check for ladders with loose, corroded, or weakened fasteners hardware (cleats, spreaders, etc.).
- Feet - Check ladders for missing or damaged feet. Ladder feet may have both nonskid pads for use on hard surfaces (concrete), and metal feet for soft surfaces (dirt).
- Coatings or Paint - check for paint or other coating hiding defects, Wood ladders shall not be painted or coated with any opaque covering, except for identification or warning labels which may be placed on one face only of a side rail. When other types of ladders are painted it is very hard for the user to observe defects/damage such as cracks or dents and painted areas must be inspected carefully for hidden damage.
- Oil, grease, and other slipping hazards - Inspect ladders for oil, grease, moisture or other slippery materials before use and clean as necessary.
- Capacity - check the capacity label and make sure the ladder has sufficient capacity to hold you and everything you are wearing/carrying.

DISCUSSION LEADER DUTIES:

Obtain a ladder and "Do Not Use" tag that you or an employee can use during the discussion to demonstrate key points.

WHAT THIS TOOLBOX TALK COVERS:

This Toolbox Talk covers pre-use inspection of ladders.

DISCUSSION NOTES:

Discuss the various negative outcomes that would result from failure to inspect ladders properly before use.



REVIEW QUESTIONS

1. It isn't necessary to inspect a ladder before use because they get inspected quarterly by the ladder competent person?

a) True

b) False: Ladders must be inspected before each use and periodically by the competent person.

2. It is okay to use a damaged ladder as long as you are not going very high.

a) True

b) False: Even "minor" falls can result in very serious injury.

3. Ladders should not be painted because the paint can cover early signs of structural failure.

a) True: Paint and other opaque coatings can hide defects and damage putting the user at risk of serious injury.

b) False

Talk Given By:	Date:
Company Name:	Location:
Printed Name	Signature

Under the Occupational Safety and Health Act, employers are responsible for providing a safe and healthy workplace and workers have rights. OSHA can help answer questions or concerns from employers and workers. OSHA's On-site Consultation Program offers free and confidential advice to small and medium-sized businesses, with priority given to high-hazard worksites. For more information, contact your regional or area OSHA office, call 1-800-321-OSHA (6742), or visit www.osha.gov.

Through the OSHA and SWR Institute Alliance, the SWR Institute developed this toolbox talk for informational purposes only. It does not necessarily reflect the official views of OSHA or the U.S. Department of Labor.

COPYRIGHT NOTICE

Copyright ©2022 by the Sealant, Waterproofing & Restoration Institute. All rights reserved. Printed in the United States of America.